


*SD Card real time data recorder
Carbon dioxide*

CO2 METER + *Humidity/Temp.*

Model : CO2-9904SD

ISO-9001, CE, IEC1010



CO2 probe



Humidity/Temp. probe



LUTRON ELECTRONIC



The Art of Measurement

SD Card real time recorder, 6000 ppm CO2 METER + Humidity/Temp.

Model : CO2-9904SD

FEATURES

* Real time recorder, save the data into the SD memory card and can be down load to the Excel, extra software is no need. User can make the further data or graphic analysis by themselves. under the Excel software.
* At the same time, the SD memory card can record three kind data (%RH/CO2/Temp.) along with the time information into the one Excel file at the same time.
* Manual datalogger is available, during execute the manual datalogger function, it can set the different location no. (position 1 to position 99).
* Air quality measurement application, multi-function : CO2 (Carbon dioxide), Humidity, temperature measurement.
* CO2 range : 0 to 6,000 ppm x 1 ppm.
* Humidity range: 10 to 95 %RH.
* Dew point Temp. and Wet bulb Temp. measurement.
* Temp. range : 0 to 50.0 °C, °C/°F.
* CO2 sensor : NDIR, long term reliability.
* Humidity sensor : Precision capacitance sensor
* Alarm setting with the beeper sound output.
* Sampling time for data recorder is 2 seconds to 8 hours.
* Complete set with 2 probes : CO2/Temp. probe, Humidity/Temp. probe, main meter and the hard carrying case.
* Separate probe, easy for remote measurement.
* Meter can cooperate with 2 GB to 16 GB SD card, SD card is optional.
* RS232/USB computer interface.
* Patented.

Advanced setting	* SD memory card Format * Set clock time * Set sampling time * Auto power OFF management * Set beep Sound ON/OFF * Decimal point of SD card setting * Temp. unit setting * Alarm value setting
@ main setting	
Operating Temperature	0 to 50 °C. (32 to 122 °F).
Operating Humidity	Less than 80% R.H.
Weight	350 g/0.77 LB.
Dimension	Meter 177 x 68 x 45 mm
	Humidity probe 197 mm in length.
	CO2 probe 190 x 38 x 28 mm
Accessories Included	Instruction manual..... 1 PC Hard carrying case, CA-08..... 1 PC CO2 probe..... 1 PC Humidity probe..... 1 PC
Optional Accessories	SD memory card (2 GB). AC to DC 9V adapter. USB cable, USB-01. RS232 cable, UPCB-02. Data Acquisition software, SW-U801-WIN.

ELECTRICAL SPECIFICATIONS (23± 5 °C)

GENERAL SPECIFICATIONS

Circuit	Custom one-chip of microprocessor LSI circuit.	
Display	LCD size : 52 mm x 38 mm LCD with green backlight (ON/OFF).	
Measurement	CO2 (Carbon dioxide) Humidity Dew point Temp., Wet bulb Temp. Temperature	
Sensor structure	CO2	NDIR * Nondispersive infrared sensor
	Humidity Temp.	Precision capacitance sensor Precision thermistor
Datalogger Sampling Time Setting range	Auto	2 sec to 8 hour 59 min. 59 sec. @ Sampling time can set to 1 second, but memory data may loss.
	Manual	Push the data logger button once will save data one time. @ Set the sampling time to 0 second. @ Manual mode, can also select the 1 to 99 position (Location) no.
Data error no.	0.1% of total saved data max.	
Memory Card	SD memory card. 1 GB to 16 GB.	
Data Hold	Freeze the display reading.	
Memory Recall	Maximum & Minimum value.	
Sampling Time of Display	Approx. 1 second.	
Data Output	RS 232/USB PC computer interface. * Connect the optional RS232 cable UPCB-02 will get the RS232 plug. * Connect the optional USB cable USB-01 will get the USB plug.	
Power Supply	* Alkaline or heavy duty DC 1.5 V battery (UM3, AA) x 6 PCs, or equivalent.	
	* DC 9V adapter input. (AC/DC power adapter is optional).	
Power Current	CO2 measurement	Normal operation (w/o SD card save data and LCD Backlight is OFF) : Approx. DC 136.5 mA.
		When SD card save the data and LCD Backlight is OFF) : Approx. DC 166 mA.
	Humidity measurement	Normal operation (w/o SD card save data and LCD Backlight is OFF) : Approx. DC 10.5 mA.
		When SD card save the data and LCD Backlight is OFF) : Approx. DC 40 mA.
* If LCD backlight on, the power consumption will increase approx. 12 mA.		

CO2 (Carbon dioxide)

CO2 (Carbon dioxide)	Range	0 to 6,000 ppm
	Resolution	1 ppm
	Accuracy	± 40 ppm
		* ≤ 1,000 ppm.
± 5% of reading * > 1,000 ppm ≤ 3,000 ppm. ± 250 ppm typically * > 3,000 ppm, reference only		
Repeatability	± 20 ppm * ≤ 3,000 ppm.	
Temperature	Range	0 °C to 50 °C, 32 °F to 122 °F.
	Resolution	0.1 degree
	Accuracy	°C : ± 0.8 °C °F : ± 1.5 °F.

Humidity/Temperature

Humidity	Range	5 % to 95 % R.H.
	Resolution	0.1 % R.H.
	Accuracy	≥ 70% RH : ± (3% reading + 1% RH). < 70% RH : ± 3% RH.
Temperature	Range	0 °C to 50 °C, 32 °F to 122 °F.
	Resolution	0.1 degree
	Accuracy	°C : ± 0.8 °C. °F : ± 1.5 °F.

Dew Point Temp. (Humidity)

°C	Range	-25.3 °C to 48.9 °C
	Resolution	0.1 °C
°F	Range	-13.5 °F to 120.1 °F.
	Resolution	0.1 °F.

Remark :

* Dew Point display value is calculated from the Humidity/Temp. measurement automatically.
* The Dew Point accuracy is sum accuracy value of Humidity & Temperature measurement..

Wet bulb Temp. (Humidity)

°C	Range	-21.6 °C to 50.0 °C
	Resolution	0.1 °C
°F	Range	-6.9 °F to 122.0 °F.
	Resolution	0.1 °F.

Remark :

* Wet bulb display value is calculated from the Humidity/Temp. measurement automatically.
* The Wet bulb accuracy is sum accuracy value of Humidity & Temperature measurement..