

SD card data recorder SD card data logger Patented SERIES



SD Card real time data logger 3 channels 4-20 mA CURRENT RECORDER Model : MMA-386SD

- * 4-20 mA current loop recorder with real time data logger, save the measuring data along the time information (year, month, date, hour, minute, second) into the SD memory card and can be downloaded to the Excel, extra software is no need.
- * Input signal : 4 to 20 mA, 3 channels.
- * Resolution : 0.01 mA.
- * Input channels : 3 channels.
- * Show 3 channels (CH1, CH2, CH3) 4-20 mA current loop values in the same LCD.
- * Records time and date stamped 4-20 mA DC current data from external sensors, transducers and many other sources.
- * Applications :
 - 4 to 20 mA recording
 - pH recording
 - Low level signal monitoring
 - Photovoltaic studies
 - Battery studies
 - Biological sensor monitoring
 - Factory process control
 - Research and development
 - Medical and Pharmaceutical
 - Environmental studies
- * Large LCD display, easy readout.
- * Low power consumption and long battery life when using battery power.
- * DC 1.5V (UM-4/AAA) battery x 6 PCs or optional DC 9V adapter in.
- * RS232/USB computer interface.
- * Size : 132 x 80 x 32 mm.



SD card real time data logger DC 300.0 mV/3000 mV 3 channels VOLTAGE RECORDER Model : MMV-387SD

- * 300.0/3000 mV recorder with real time data logger, save the measuring data along the time information (year, month, date, hour, minute, second) into the SD memory card and can be downloaded to the Excel, extra software is no need.
- * Input signal : 300.0 mV/3000 mV, 3 channels.
- * Resolution : 0.1 mV/1 mV.
- * Show 3 channels (CH1, CH2, CH3) mV measurement values in the same LCD.
- * Records time and date along DC mV value from external sensors, transducers and many other sources.
- * Large LCD display, easy readout.
- * Applications :
 - 300.0 mV/3000 DC mV recording.
 - Current probe recording
 - pH recording
 - Low level signal monitoring
 - Photovoltaic studies
 - Battery studies
 - Biological sensor monitoring
 - Factory process control
 - Research and development
 - Medical and Pharmaceutical
 - Environmental studies
- * Low power consumption and long battery life when using battery power.
- * DC 1.5V (UM-4/AAA) battery x 6 PCs or optional DC 9V adapter in.
- * RS232/USB computer interface.