

pH 4, pH 7 BUFFER SOLUTION

Model : PH-04, PH-07

ISO-9001, CE, IEC1010



pH 4.00 BUFFER SOLUTION		
Model : PH-04		
Temperature		pH value
0 °C	32 °F	4.01 pH
5 °C	41 °F	3.99 pH
10 °C	50 °F	4.00 pH
15 °C	59 °F	3.99 pH
20 °C	68 °F	4.00 pH
25 °C	77 °F	4.00 pH
30 °C	86 °F	4.01 pH
35 °C	95 °F	4.02 pH
40 °C	104 °F	4.03 pH
50 °C	122 °F	4.06 pH
60 °C	140 °F	4.09 pH
Material content	Potassium Biphthalate Buffer	
Standard Traceable to N.I.S.T.		
Accuracy +/- 0.01 pH		

Model : PH-04

* pH 4.00 buffer solution.



pH 7.00 BUFFER SOLUTION		
Model : PH-07		
Temperature		pH value
0 °C	32 °F	7.01 pH
5 °C	41 °F	7.99 pH
10 °C	50 °F	7.00 pH
15 °C	59 °F	7.99 pH
20 °C	68 °F	7.00 pH
25 °C	77 °F	7.00 pH
30 °C	86 °F	7.01 pH
35 °C	95 °F	7.02 pH
40 °C	104 °F	7.03 pH
50 °C	122 °F	7.06 pH
60 °C	140 °F	7.09 pH
Material content	Potassium Biphthalate Buffer	
Standard Traceable to N.I.S.T.		
Accuracy +/- 0.01 pH		

Model : PH-07

* pH 7.00 buffer solution.



Lutron

LUTRON ELECTRONIC

The Art of Measurement